

CDD12J/CDD12JD

全电动堆垛车 Electric pallet stacker

产品性能特点:

1. 大功率、高性能起升泵站，操作效率高；
2. 侧驾驱动设计，转弯半径小，视野广；
3. 永磁电机驱动系统，体积小、质量轻、损耗小；
4. 德国原装进口防水微动开关，适应寒冷、潮湿、粉尘等恶劣环境；
5. 四色显示LED电量表，简单直观；
6. 外置式充电器，散热性能更佳；
7. 超长操作手柄，集成起升按钮、钥匙开关、电量表，符合人机工程学原理，操作简单舒适；加装龟速开关，速度控制更精准；采用优质气压式弹簧，自动缓慢复位，经久耐用。
8. 高密度铁丝防护网，编焊而成，坚固耐用，防护效果优良；

Characteristics:

1. High-power and high-performance lifting pump has high efficiency.
2. Side driving design gives the truck a small steering radius and broadened view.
3. The driving system with permanent magnetic motor has small volume, light mass, small loss.
4. Water-proof inching switch imported from German meets the requirements of harsh working condition such as cold, humidity and dust circumstances.
5. Four colors LED electricity meter makes it simple and direct to read.
6. External positioned charger has better cooling performance.
7. It's more comfortable and easy for operation using a super long handle that integrates lifting button, key switch, electricity meter, which is suitable for ergonomics; more accurate speed control with the turtle speed switch; more durable with the high quality air-pressure springs which allows slowly and automatically reset.
8. Iron steel guard with high density is durable, firm and has high protection effect.





CDD12J/CDD12JD

全电动堆垛车 Electric pallet stacker

制造商和技术参数 Manufacturer's Data and Design Characteristics

特征 Characteristics		合力 Heli						
1.01 品牌 Manufacturer		合力 Heli						
1.02 车型 Model		CDD12J					CDD12JD	
1.03 操作方式 Operation		步行式 Pedestrian propelled						
1.04 额定载荷能力 Rated traction weight	Q (kg)	1200						
1.05 门架类型 Mast type		单门架 Single mast	两级标准 2-Stage STD					单立柱 Single column
1.06 提升高度 Lift	h3 (mm)	1600	2000	2500	3000	3500	1600	
1.07 最高点载重量 Capacity at highest height	kg	1200	1050	900	750	600	1200	
1.08 自重(含电瓶) Service weight with battery	kg	425	441	453	465	477	395	
1.09 载荷中心距 Load centre	c (mm)	600						
1.10 前悬距 Axle centre to fork face	x (mm)	710						
1.11 轴距 Wheel base	y (mm)	1154					1031	
轮子/底盘 Wheels/Tyres		聚氨酯 Polyurethane						
2.01 轮胎类型 Wheels type		聚氨酯 Polyurethane						
2.02 驱动轮尺寸 Driving wheel size	Φ × w (mm)	Φ210 × 70						
2.03 承载轮尺寸 Bearing wheel size	Φ × w (mm)	Φ80 × 70						
2.04 平衡轮尺寸 Additional wheels (dimensions)	Φ × w (mm)	Φ150 × 58						
2.05 驱动轮, 平衡轮/承载轮数量 (x=驱动轮) Wheels, number front/rear (x=driven)		1x+1/4						
尺寸 Dimensions								
3.01 最低门架高度 lowered Height of mast, lowered	h1 (mm)	2014	1494	1744	1994	2244	1990	
3.02 门架最大高度 Height of mast, extended	h4 (mm)	2014	2424	2924	3424	3924	2060	
3.03 货叉最低高度 Fork Height, Lowered	h13 (mm)	86						
3.04 整车长度 Overall length	l1 (mm)	1755					1632	
3.05 车体长度 Length to fork face	l2 (mm)	605					482	
3.06 整体宽度 Overall width	b1/ b2 (mm)	795						
3.07 货叉尺寸 Fork dimensions	s/e/l (mm)	60/160/1150						
3.08 货叉外宽 Width of forks	b5 (mm)	570/695						
3.09 轴距中心处离地间隙 Min. Ground clearance	m2 (mm)	24						
3.10 通道宽度: 1000x1200托盘 (1200跨货叉放置) Aisle width with pallet 1000x1200 across forks	Ast (mm)	2068					2048	
3.11 通道宽度: 800x1200托盘 (1200沿货叉放置) Aisle width with pallet 800x1200 along forks	Ast (mm)	2034					2014	
3.12 转弯半径 Min. Turning radius	Wa (mm)	1366					1316	
性能 Performance								
4.01 行走速度, 满载/空载 Travel speed, with/without load	(km/h)	4.0/4.2						
4.02 提升速度, 满载/空载 Lifting speed, with/without load	(mm/s)	92/136						
4.03 下降速度, 满载/空载 Lowering speed, with/without load	(mm/s)	112/98						
4.04 最大爬坡能力 Max. gradeability laden/unladen	(%)	6/8						
4.05 制动类型 Service brake		电磁制动 Electromagnetic brake						
电机 Drive								
5.01 驱动电机功率 Drive motor output S2 60 min.	(kW)	0.75						
5.02 起升电机功率 Lift motor rating at S3 15%	(kW)	2.2						
5.03 蓄电池, 根据DIN 43531/35/36 A,B,C,no Battery according to DIN 43531/35/36 A,B,C,no		no						
5.04 蓄电池电压/容量 Battery voltage/rated capacity	(V/Ah)	2 × 12/100						
5.05 蓄电池重量 (±5%) Battery weight (±5%)	(kg)	2 × 27						
其他 Others								
6.01 噪音水平 Noise level at operator's ear	(dB(A))	69						
6.02 转向类型 Steering type		机械转向 Mechanical steering						



HELI 安徽合力股份有限公司
ANHUI HELI CO., LTD.

地址: 中国合肥经开区方兴大道668号
电话: (86 551)63632133, 63648005, 63689000
传真: (86 551)63633431
服务: 4001-600761
网址: http://www.helichina.com

ADD: NO. 668 Fangxing Street, Economical Development Zone, Hefei, P.R. China
TEL: (86 551)63632133, 63648005, 63689000
FAX: (86 551)63633431
400 SERVICE: 4001-600761
WEBSITE: http://www.helichina.com

授权经销商 AUTHORIZED DEALER

* 本公司保留更改产品设计和规格的权利, 恕不另行通知。
* Our products are subject to improvements and changes without notice.